

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
2 June 2005 (02.06.2005)

PCT

(10) International Publication Number
WO 2005/050283 A1

- (51) International Patent Classification⁷: **G02B 26/08**, H01L 41/12
- (21) International Application Number:
PCT/NL2003/000819
- (22) International Filing Date:
21 November 2003 (21.11.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): **NED-ERLANDSE ORGANISATIE VOOR TOEGEPAST-NATUURWETENSCHAPPELIJK ONDERZOEK TNO** [NL/NL]; Schoemakerstraat 97, NL-2628 VK Delft (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **HAMELINCK, Roger, Franciscus, Mattheus, Maria** [NL/NL]; Oranjeplein 48, NL-5104 HJ Dongen (NL). **ROSIELLE, Petrus, Carolus, Johannes, Nicolaas** [NL/NL]; Kapteynlaan 25, NL-5505 AV Veldhoven (NL). **KAPPELHOF, Jakobus, Pieter** [NL/NL]; Nassaukade 41, NL-2281 XD Rijswijk (NL).
- (81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, EG, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SURFACE DEFORMATION ACTUATION STRUCTURE



(57) Abstract: A structure such as an electronically deformable mirror contains a deformable membrane, an array of actuators located facing the membrane, each actuator being arranged to actuate local displacement of the membrane perpendicular to its surface. The actuators and the membrane are connected via an array of actuating connections. The actuating connections substantially transmit movement perpendicular to the second surface, but leave planar displacement and/or local rotation of the second surface substantially free. Preferably, the actuators contain an array of soft magnetic islands on a soft magnetic base plane, with actuator coils running around the islands and a system of sort magnetic walls on the base plane to separate the coils. The walls support a soft magnetic resilient surface that extend over of the islands and serve to drive the actuating connections. Preferably the base plane is supported on an array of rod shaped connection elements, leaving space to permit air to circulate between the support structures and the support plate.

WO 2005/050283 A1